

## 3.5" USB 2.0 External Enclosure

**Model : XE311U**



### Feature

- *Easy assembly.*
- *Supporting 3.5" IDE hard disk drives*
- *Silent operation with aluminum housing and tray*
- *Compliance with USB 2.0 electrical specification*
- *Support USB High-Speed and Full-Speed Operation*
- *Compliance with USB Mass Storage Class, Bulk-Only Transport Specification*
- *Plug and play; hot-swappable connection*
- *Easy One-Touch backup to copy/save files (specified models only)*

### Specifications

- *Interface: USB 2.0*
- *HDD: IDE HDD*
- *Power Supply: External 12V/2A AC adapter*
- *Chipset: JMicron JM20335*
- *Platforms: Windows XP/2000/Me/98SE/ Mac OS X or above*
- *Display: LED display (power, HDD access)*
- *Case material: Aluminum*
- *Dimensions: 9.2" (L) x 5.1" (W) x 1.5" (H) / 232.5 mm (L) x 130.5 mm (W) x 37 mm (H)*

## 3.5" USB 2.0 +1394a Combo External Enclosure

**Model : XE311C / XE311F**



### Feature

- Easy assembly.
- Supporting 3.5" IDE hard disk drives
- Silent operation with aluminum housing and tray
- Provides hot-swap function to select active device USB or 1394.
- Provides auto-detect function to select active device between USB and 1394.
- IEEE 1394-1995 and IEEE P1394a compliant.
- USB 1.1 and USB 2.0 compliant.
- USB Mass Storage Class Bulk-Only Transport Specification Compliant.
- Generic driver support for Microsoft Windows 98SE above, Apple MacOS and Linux.
- (Windows 98SE need vendor driver for USB)

### Specifications

- Interface: USB 2.0 + 1394a combo
- HDD: IDE HDD
- Power Supply: External 12V/2A AC adapter
- Chipset: PL3507 + TSB41AB2
- Platforms: Windows XP/2000/Me/98SE/ Mac OS X or above/ Linux
- Display: LED display (power, HDD access)
- Case material: Aluminum
- Dimensions: 9.2" (L) x 5.1" (W) x 1.5" (H) / 232.5 mm (L) x 130.5 mm (W) x 37 mm (H)

## 3.5" Dual interface- eSATA and USB 2.0 External Enclosure

**Model : XE311SU**



### Feature

- Easy assembly.
- Supporting 3.5" SATA hard disk drives
- Silent operation with aluminum housing and tray
- Dual interface: eSATA and USB 2.0
- Maximum transfer rate up to 3Gbits/s (eSATA) or 480 Mbits/s (USB 2.0)
- Plug and play; hot-swappable connection
- Easy One-Touch backup to copy/save files (specified models only)

### Specifications

- Interface: SATA HDD to eSATA + USB 2.0
- HDD: SATA HDD
- Power Supply: External 12V/2A AC adapter
- Chipset: Oxford OXU921DS or J Micron JM20336
- Platforms: Windows XP/2000/Me/98SE/ Mac OS X or above
- Display: LED display (power, HDD access)
- Case material: Aluminum
- Dimensions: 9.2" (L) x 5.1" (W) x 1.5" (H)  
232.5 mm (L) x 130.5 mm (W) x 37 mm (H)