

# ATX Mid Tower Case

Model : ECE4572

**TAC 2.0 Chassis ready :**  
For Intel® Core™ i7 Processor  
Thermally Advantaged Chassis



Case Inside View :

## Feature

- ◀ Mechanical and thermal test approved by Intel®
- ◀ All around folded metal edge for safety installation.
- ◀ Screwless front panel and side door for quick assembly.
- ◀ Screwless/tool-less designs to minimize assembly time.
- ◀ Optional supporting bar with 3 various length card holders.
- ◀ Installing optional 8, 9 or 12 cm fan on Front & Rear side for excellent cooling.
- ◀ Detachable tool free HDD drive cage with optional shockproof rubber kits.
- ◀ Optional front I/O access– Supporting
  - a. Azalia Front I/O Kit : 2\* USB (v2.0 or v3.0) + 2\* HD Audio + Firewire (IEEE1394)
  - b. Azalia Front I/O Kit : 2\* USB (v2.0 or v3.0)+ 2\* HD Audio
  - c. Azalia Front I/O Kit : 4\* USB (v2.0 or v3.0) + 2\* HD Audio
  - d. Azalia Front I/O kit: 2\* USB (v2.0 or v3.0) + HD audio + eSATA
- ◀ Complies with RoHS, CE, and FCC requirements

## Specification

Model No.	ECE4572
Drive Space	4 x 5.25"(Exposed) + 2 x 3.5 " (Exposed) + 2 x 3.5" (Hidden) + 2 Optional 3.5" (Hidden) ** Up to 10 Drive Bays (CD-ROM/DVD's less than 190.5 mm /7.5" In depth are recommended at 3rd and 4th 5.25"Bays)
M/B Accept:	Micro ATX / Standard ATX M/B (12" x 9.6")
Power Supply:	ATX 12V Switching Power
Ventilation ( optional )	Front / Rear: 8, 9 or 12cm Fan x 1
Measurement	192 mm (W) x 482 mm(D) x 426 mm(H) 7.5"(W) x 19.6" (D) x 16.8" (H)
Weight(NW/GW)	8.2/9.2 kg • 18.0/20.2 lb (w/o Power Supply)
Standard Packing	2.47 cu.ft./pc 407 pcs/20 ft. Container., 839 pcs/40 ft. Container 935 pcs/40 ft. high cu.ft. Container
Bulk(OEM) Packing	480 pcs/20 ft. Container 1056 pcs/40 ft. Container